


INEX>DECKING™

ANY BUILDING • ANY SURFACE • ANYWHERE

RECOMMENDED CLEAR COATING SYSTEM – EPIMAX

This sheet provides the recommended procedures and coating system to deliver a clear sealed finish to **INEX>DECKING**. This system uses products from EpiMax range of Coatings and Protection Systems. EpiMax can be contacted at 1300 721 522.



BEFORE



AFTER

INSIDE WORK

1. Polyvac floor sander or similar with 80 grit sandpaper
2. Apply EM 999UVX Gloss ... 10m²/L ... allow to harden
3. Apply EM 999UVX Gloss or Matt ... 10m²/L... allow to harden

Note: If a wet area, consider adding EM Additive #50 4% w/w

OUTSIDE WORK

Decking or Walls

1. Apply EM 900 Gloss ... all sides ... 10 m²/L ... allow to harden
2. Fix boards
3. Apply EM 900 Gloss ... 12 m²/L ... allow to harden
4. Apply EM 900 Gloss or Satin ... 12 m²/L ... allow to harden

Note: If a wet Deck area, consider adding EM Additive #50 4% w/w

INEX > BOARDS™

National Head Office

62 Belmore Road Punchbowl NSW 2196

www.inexboards.com.au Phone 1300 463 923



BRICKWORKS
BUILDING PRODUCTS

Range of building products:

proud supporters



BOWRAL BRICKS

Pronto Panel™

INEX > BOARDS
