

INEX>RENDERBOARD™

ANY BUILDING • ANY SURFACE • ANYWHERE

RECOMMENDED CLEAR COATING SYSTEM – EPIMAX

This sheet provides the recommended procedures and coating system to deliver a clear sealed finish to the SMOOTH SIDE of **INEX>RENDERBOARD** for external applications. This system uses products from the EpiMax range of Coatings and Protection Systems. EpiMax can be contacted at 1300 721 522.



STEP 1 – Prepare

Ensure all surfaces are clean and dust free. Simply wipe with a 50/50 solution of water and white vinegar and allow to dry. Store in a sheltered dry area and do not let the boards absorb excessive moisture prior to Step 2.

STEP 2 – Coat 1

PRIOR TO ASSEMBLY apply a first coat of EpiMax 900 Gloss all sides and the smooth face of the **INEX>RENDERBOARD** – coverage about 10m²/litre. Use a brush on the edges to ensure penetration into the tongue and groove profiles. Otherwise use a foam roller for the smooth face. During assembly coat all cut edges prior to fixing in place.

STEP 3 – Coat 2

AFTER ASSEMBLY apply a further coat of EpiMax 900 – coverage about 12+ m²/litre ensuring any screw fixings are well sealed. If at this stage due to absorption of the EpiMax into **INEX>RENDERBOARD** further coats are required, simply apply a further coat of EpiMax 900.

NOTE: EpiMax 900 is also available in Satin to suit the desired final finish, but the first coat must be applied with EpiMax 900 Gloss.

INEX > BOARDS™

National Head Office

62 Belmore Road Punchbowl NSW 2196

www.inexboards.com.au Phone 1300 463 923



BRICKWORKS
BUILDING PRODUCTS

Range of building products:

proud supporters



BOWRAL BRICKS

Pronto Panel™

INEX > BOARDS
