

Product Name: Burradoo | Size: 230 × 110 × 76mm | Manufactured: NSW







Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Name: Bargo | Size: 230 × 110 × 76mm | Manufactured: NSW






Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Range: Bowral Blends

Product Name: Exeter | Size: 230 × 110 × 76mm | Manufactured: NSW







Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Range: Bowral Blends

Product Name: Berrima | Size: 230 × 110 × 76mm | Manufactured: NSW






Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Range: Bowral Blends

Product Name: Kangaloon | Size: 230 × 110 × 76mm | Manufactured: NSW







Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Range: Bowral Blends

Product Name: Hill Top | Size: 230 × 110 × 76mm | Manufactured: NSW






Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Range: Bowral Blends

Product Name: Wilton | Size: 230 × 110 × 76mm | Manufactured: NSW






Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Name: Mt Broughton | Size: 230 × 110 × 76mm | Manufactured: NSW






Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade



Product Name: Picton | Size: 230 × 110 × 76mm | Manufactured: NSW





Typical Properties	
Length (mm)	230mm
Width (mm)	110mm
Height (mm)	76mm
Dimensional Category	DW1
Average Weight / Unit (kg)	3.8
Units per Square Metre	48.5
Pack Size	400
Characteristic Unconfined Compressive Strength (f'uc) MPa	>12
Maximum Cold Water Absorption (%)	<15
Initial Rate of Absorption (IRA) (kg/m² min)	3.0 - 8.0
Coefficient of Expansion e'Factor (mm/m)	<1.0
Core Volume (%)	Solid
Liability to Efflorescence	Slight
Lime Pitting Liability	Slight
Solar Absorptance Rating	NA
Durability Class	Exposure Grade

