


Product Details

range name	GREY BLOCK
product code description	10-01 90MM GREY STANDARD

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 200 x 400
actual dimensions (length x width x height mm)	90 x 190 x 390
core volume (% overall thickness)	<30
characteristic unconfined compressive strength (MPa)	> 15
minimum shell thickness (mm)	25
average weight (KG)	9.8
units per tonne	102
number per pallet	160
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	130
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	10-02

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 200 x 300
actual dimensions (length x width x height mm)	90 x 190 x 290
core volume (% overall thickness)	<30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	8.5
units per tonne	117.6470588235294
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	10-03 90MM HALF

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 200 x 200
actual dimensions (length x width x height mm)	90 x 190 x 190
core volume (% overall thickness)	<30
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	30
average weight (KG)	4.9
units per tonne	204
number per pallet	360
number per sqm/lm	25
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	10-25

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 200 x 400
actual dimensions (length x width x height mm)	90 x 190 x 390
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	14.4
units per tonne	69.44444444444444
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	10-31

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 200 x 400
actual dimensions (length x width x height mm)	90 x 190 x 390
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	14.8
units per tonne	67.56756756756756
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	10-34

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 200 x 100
actual dimensions (length x width x height mm)	90 x 190 x 90
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	3.4
units per tonne	294.1176470588235
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	10-71 90MM STANDARD HALF HEIGHT

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 100 x 400
actual dimensions (length x width x height mm)	90 x 90 x 390
core volume (% overall thickness)	28
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	25
average weight (KG)	5.3
units per tonne	189
number per pallet	360
number per sqm/lm	25 or 2.5/lineal meter as caps
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	147
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-01 140MM STANDARD

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 200 x 400
actual dimensions (length x width x height mm)	140 x 190 x 390
core volume (% overall thickness)	42
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	25
average weight (KG)	14.3
units per tonne	70
number per pallet	120
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	186
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-02

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 300 x 400
actual dimensions (length x width x height mm)	190 x 290 x 290
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	9.7
units per tonne	103.0927835051546
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-03 140MM HALF

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 200 x 200
actual dimensions (length x width x height mm)	140 x 190 x 190
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	30
average weight (KG)	7.7
units per tonne	130
number per pallet	240
number per sqm/lm	25
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-12 140MM GREY LINTEL

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 200 x 400
actual dimensions (length x width x height mm)	140 x 190 x 390
core volume (% overall thickness)	24
characteristic unconfined compressive strength (MPa)	> 15
minimum shell thickness (mm)	40
average weight (KG)	15.7
units per tonne	64
number per pallet	100
number per sqm/lm	2.5/lineal meter
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	208
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-20 140MM GREY KNOCKOUT

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 200 x 400
actual dimensions (length x width x height mm)	140 x 190 x 390
core volume (% overall thickness)	49
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	25
average weight (KG)	12.2
units per tonne	82
number per pallet	120
number per sqm/lm	2.5/lineal meter
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	159
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-22

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 200 x 350
actual dimensions (length x width x height mm)	140 x 190 x 340
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	9.6
units per tonne	104.166666666667
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-25

Properties and Specifications

nominal dimensions (length x width x height mm)	110 x 200 x 400
actual dimensions (length x width x height mm)	100 x 190 x 390
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	15.6
units per tonne	64.1025641025641
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-38

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 110 x 200
actual dimensions (length x width x height mm)	190 x 100 x 190
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-48 140MM GREY H BLOCK

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 200 x 400
actual dimensions (length x width x height mm)	140 x 190 x 390
core volume (% overall thickness)	40
characteristic unconfined compressive strength (MPa)	> 15
minimum shell thickness (mm)	30
average weight (KG)	12.7
units per tonne	78
number per pallet	120
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	168
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-71 140MM STANDARD HALF HEIGHT

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 100 x 400
actual dimensions (length x width x height mm)	140 x 90 x 390
core volume (% overall thickness)	44
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	25
average weight (KG)	7.2
units per tonne	140
number per pallet	240
number per sqm/lm	25 or 2.5/lineal meter as caps
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	193
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-73 140MM GREY HALF HEIGHT HALF

Properties and Specifications

nominal dimensions (length x width x height mm)	150x200x400
actual dimensions (length x width x height mm)	140 x 90 x 190
core volume (% overall thickness)	39
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	25
average weight (KG)	3.1
units per tonne	323
number per pallet	480
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-738

Properties and Specifications

nominal dimensions (length x width x height mm)	110 x 221 x 160
actual dimensions (length x width x height mm)	100 x 211 x 150
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.

Product Details

range name	GREY BLOCK
product code description	15-739

Properties and Specifications

nominal dimensions (length x width x height mm)	150 x 200 x 300
actual dimensions (length x width x height mm)	140 x 190 x 290
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-81

Properties and Specifications

nominal dimensions (length x width x height mm)	
actual dimensions (length x width x height mm)	
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	15-934

Properties and Specifications

nominal dimensions (length x width x height mm)	
actual dimensions (length x width x height mm)	
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-01 190MM STANDARD

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 200 x 400
actual dimensions (length x width x height mm)	190 x 190 x 390
core volume (% overall thickness)	47
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	30
average weight (KG)	15.6
units per tonne	64
number per pallet	90
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	204
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-02 190MM THREE QUARTER

Properties and Specifications

nominal dimensions (length x width x height mm)	200x200x300
actual dimensions (length x width x height mm)	190x190x290
core volume (% overall thickness)	48
characteristic unconfined compressive strength (MPa)	> 15
minimum shell thickness (mm)	
average weight (KG)	11.2
units per tonne	89.28571428571429
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-03 190MM HALF

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 200 x 200
actual dimensions (length x width x height mm)	190 x 190 x 190
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	30
average weight (KG)	8.7
units per tonne	115
number per pallet	180
number per sqm/lm	25
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-04

Properties and Specifications

nominal dimensions (length x width x height mm)	100 x 100 x 200
actual dimensions (length x width x height mm)	90 x 90 x 190
core volume (% overall thickness)	Nil
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-12 190MM GREY TROUGH BEAM

Properties and Specifications

nominal dimensions (length x width x height mm)	200x200x400
actual dimensions (length x width x height mm)	190x190x390
core volume (% overall thickness)	40
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	30
average weight (KG)	17.8
units per tonne	56.17977528089887
number per pallet	108
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-13

Properties and Specifications

nominal dimensions (length x width x height mm)	200x200x200
actual dimensions (length x width x height mm)	190x190x190
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	18.5
units per tonne	54.05405405405406
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-16

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 200 x 400
actual dimensions (length x width x height mm)	190 x 190 x 390
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-18

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 400 x 200
actual dimensions (length x width x height mm)	190 x 390 x 190
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-19

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 300 x 200
actual dimensions (length x width x height mm)	190 x 290 x 190
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-20 190MM GREY KNOCKOUT

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 200 x 400
actual dimensions (length x width x height mm)	190 x 190 x 390
core volume (% overall thickness)	41
characteristic unconfined compressive strength (MPa)	> 15
minimum shell thickness (mm)	30
average weight (KG)	13.4
units per tonne	75
number per pallet	90
number per sqm/lm	2.5/lineal meter
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	175
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-21 190MM CORNER KNOCKOUT BOND BEAM

Properties and Specifications

nominal dimensions (length x width x height mm)	200x200x400
actual dimensions (length x width x height mm)	190x190x390
core volume (% overall thickness)	78
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	31
average weight (KG)	15.1
units per tonne	76
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-22

Properties and Specifications

nominal dimensions (length x width x height mm)	200x200x350
actual dimensions (length x width x height mm)	190x190x340
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-31

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 200 x 400
actual dimensions (length x width x height mm)	190 x 190 x 390
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-38

Properties and Specifications

nominal dimensions (length x width x height mm)	190 x 100 x 245
actual dimensions (length x width x height mm)	190 x 100 x 245
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.

Product Details

range name	GREY BLOCK
product code description	20-40

Properties and Specifications

nominal dimensions (length x width x height mm)	78 x 102 x 190
actual dimensions (length x width x height mm)	78 x 102 x 190
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	14.1
units per tonne	70.92198581560284
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-42 190MM CHANNEL

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 200 x 400
actual dimensions (length x width x height mm)	190 x 190 x 390
core volume (% overall thickness)	48
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	30
average weight (KG)	15.6
units per tonne	64
number per pallet	90
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	204
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-48 190MM GREY H BLOCK

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 200 x 400
actual dimensions (length x width x height mm)	190 x 190 x 390
core volume (% overall thickness)	56
characteristic unconfined compressive strength (MPa)	> 15
minimum shell thickness (mm)	30
average weight (KG)	12.8
units per tonne	78
number per pallet	75
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	169
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-60

Properties and Specifications

nominal dimensions (length x width x height mm)	190 x 190 x 390 x 190 x 200
actual dimensions (length x width x height mm)	190 x 190 x 390 x 190 x 200
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-61

Properties and Specifications

nominal dimensions (length x width x height mm)	190 x 190 x 390
actual dimensions (length x width x height mm)	190 x 190 x 390
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	20.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-71 190MM STANDARD HALF HEIGHT

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 100 x 400
actual dimensions (length x width x height mm)	190 x 90 x 390
core volume (% overall thickness)	47
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	30
average weight (KG)	8.0
units per tonne	125
number per pallet	180
number per sqm/lm	25 or 2.5/lineal meter as caps
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	218
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-724

Properties and Specifications

nominal dimensions (length x width x height mm)	190 x 190 x 190
actual dimensions (length x width x height mm)	190 x 190 x 190
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-73

Properties and Specifications

nominal dimensions (length x width x height mm)	200 x 100 x 200
actual dimensions (length x width x height mm)	190 x 90 x 190
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	4.0
units per tonne	250
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-739

Properties and Specifications

nominal dimensions (length x width x height mm)	100x200x200x210x10x300
actual dimensions (length x width x height mm)	90x190x190x210x50x290
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-749

Properties and Specifications

nominal dimensions (length x width x height mm)	190 x 90 x 210
actual dimensions (length x width x height mm)	190 x 90 x 210
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	20-925

Properties and Specifications

nominal dimensions (length x width x height mm)	200x200x400
actual dimensions (length x width x height mm)	190x190x390
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	50-31

Properties and Specifications

nominal dimensions (length x width x height mm)	190 x 40 x 390
actual dimensions (length x width x height mm)	190 x 40 x 390
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	7.4
units per tonne	135.1351351351351
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	30-01 290MM STANDARD

Properties and Specifications

nominal dimensions (length x width x height mm)	300 x 200 x 400
actual dimensions (length x width x height mm)	290 x 190 x 390
core volume (% overall thickness)	52
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	40
average weight (KG)	20.0
units per tonne	50
number per pallet	60
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	262
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	30-02 290MM 3/4

Properties and Specifications

nominal dimensions (length x width x height mm)	300x200x300
actual dimensions (length x width x height mm)	290x190x290
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	30-04

Properties and Specifications

nominal dimensions (length x width x height mm)	100x200x300
actual dimensions (length x width x height mm)	90x190x290
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	30-20 290MM GREY KNOCKOUT

Properties and Specifications

nominal dimensions (length x width x height mm)	300 x 200 x 400
actual dimensions (length x width x height mm)	290 x 190 x 390
core volume (% overall thickness)	59
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	40
average weight (KG)	22.1
units per tonne	45
number per pallet	50
number per sqm/lm	2.5/lineal meter
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	236
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	30-48 290MM H BLOCK

Properties and Specifications

nominal dimensions (length x width x height mm)	300 x 200 x 400
actual dimensions (length x width x height mm)	290 x 190 x 390
core volume (% overall thickness)	54
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	35
average weight (KG)	22.2
units per tonne	45
number per pallet	60
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	288
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	30-72

Properties and Specifications

nominal dimensions (length x width x height mm)	300 x 100 x 300
actual dimensions (length x width x height mm)	290 x 90 x 290
core volume (% overall thickness)	
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	30-925 290MM GREY STANDARD

Properties and Specifications

nominal dimensions (length x width x height mm)	300 x 200 x 400
actual dimensions (length x width x height mm)	290 x 190 x 390
core volume (% overall thickness)	55
characteristic unconfined compressive strength (MPa)	>15
minimum shell thickness (mm)	40
average weight (KG)	19.5
units per tonne	51
number per pallet	50
number per sqm/lm	12.5
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	255
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.


Product Details

range name	GREY BLOCK
product code description	40-925

Properties and Specifications

nominal dimensions (length x width x height mm)	200x200x400x400
actual dimensions (length x width x height mm)	190x190x390x390
core volume (% overall thickness)	>30
characteristic unconfined compressive strength (MPa)	
minimum shell thickness (mm)	
average weight (KG)	0.0
units per tonne	
number per pallet	
number per sqm/lm	
durability class (to AS4456.10 - sodium sulphate and sodium chloride)	GENERAL PURPOSE
wall mass inc mortar hollow	
characteristic unconfined compressive strength (FUC)	
Light Reflectance Value	-

Diagram



Fire Resistance Levels

Structural Adequacy (see notes)	60 to 240
Integrity	60
Insulation	60

Notes

Maximum Slenderness ratio (Srf) of hollow masonry, from AS3700:2011, Table 6.1, is:
 18.0 at 60 minutes
 17.0 at 90 minutes
 16.0 at 120 minutes
 15.5 at 180 minutes
 15.5 at 240 minutes

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf <36: 240 minutes.