

Product Details

range name	1.58M X 200MM X 75MM
finish	2M X 200MM X 75MM
colours	GRAPHITE, NATURAL
product code description	1.58M X 200MM X 75MM SANDSTONE NEVER GOES OUT OF STYLE. DESIGN AN ELEGANT, EARTHY LOOK WITH THE WARM COLOURS AND TEXTURES FOUND IN SANDSTONE EFFECT CONCRETE SLEEPERS. FEATURING A BLOCK FACE PATTERN, AND AVAILABLE IN NATURAL OR GRAPHITE, SANDSTONE EFFECT CONCRETE SLEEPERS ARE MANUFACTURED USING 40MPA CONCRETE AND REINFORCED WITH STEEL FOR STRENGTH AND DURABILITY.

Diagram



Properties and Specifications

work size dimensions (length x width x height mm)	1580X75X200MM
characteristic unconfined compressive strength (MPa)	40
average weight (KG)	53.0
number per sqm/lm	3.16
number per pallet	
units per tonne	18.87

Manufactured to AS/NZS 4455.3: 2008. Tested as per AS/NZS 4456: 2003.

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact Austral Masonry for confirmation of product specification.

Product Details

range name	2M X 200MM X 75MM
finish	2M X 200MM X 75MM
colours	NATURAL, GRAPHITE
product code description	2M X 200MM X 75MM SANDSTONE NEVER GOES OUT OF STYLE. DESIGN AN ELEGANT, EARTHY LOOK WITH THE WARM COLOURS AND TEXTURES FOUND IN SANDSTONE EFFECT CONCRETE SLEEPERS. FEATURING A BLOCK FACE PATTERN, AND AVAILABLE IN NATURAL OR GRAPHITE, SANDSTONE EFFECT CONCRETE SLEEPERS ARE MANUFACTURED USING 40MPA CONCRETE AND REINFORCED WITH STEEL FOR STRENGTH AND DURABILITY.

Diagram



Properties and Specifications

work size dimensions (length x width x height mm)	2000X75X200MM
characteristic unconfined compressive strength (MPa)	40
average weight (KG)	68.0
number per sqm/lm	2.5
number per pallet	
units per tonne	14.71

Manufactured to AS/NZS 4455.3: 2008. Tested as per AS/NZS 4456: 2003.

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact Austral Masonry for confirmation of product specification.