

Product Details

range name	PIONEER
finish	SMOOTH
colours	CHARCOAL, GREY
product code description	PIONEER SMOOTH 1.2M STANDARD UNIT

Diagram



Properties and Specifications

actual dimensions (length x width x height mm)	1200 X 200 X 75MM
dimensional category	-
average weight (KG)	40
durability class	General Purpose
number per sqm/lm	4.7
number per pallet	-
number per tonne	25
characteristics breaking load (kN)	-
mean cold water absorption (%)	-
mean abrasion resistance (CM ³)	-
characteristic unconfined compressive strength (MPa)	40
	-

Tested as per AS/NZS 4456: 2003 and 4586: 2013.

*This data represents average results from production lots based on the results achieved by samples selected at random for testing.
Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification*

Product Details

range name	PIONEER
finish	SMOOTH
colours	CHARCOAL, GREY
product code description	PIONEER SMOOTH 1.53M STANDARD UNIT

Diagram



Properties and Specifications

actual dimensions (length x width x height mm)	1530 X 200 X 75MM
dimensional category	-
average weight (KG)	49
durability class	General Purpose
number per sqm/lm	3.27
number per pallet	-
number per tonne	20.41
characteristics breaking load (kN)	-
mean cold water absorption (%)	-
mean abrasion resistance (CM ³)	-
characteristic unconfined compressive strength (MPa)	40
	-

Tested as per AS/NZS 4456: 2003 and 4586: 2013.

*This data represents average results from production lots based on the results achieved by samples selected at random for testing.
Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification*

Product Details

range name	PIONEER
finish	SMOOTH
colours	CHARCOAL, GREY
product code description	PIONEER SMOOTH 2M STANDARD UNIT

Diagram



Properties and Specifications

actual dimensions (length x width x height mm)	2000 X 200 X 75MM
dimensional category	-
average weight (KG)	67
durability class	General Purpose
number per sqm/lm	2.5
number per pallet	-
number per tonne	14.93
characteristics breaking load (kN)	-
mean cold water absorption (%)	-
mean abrasion resistance (CM ³)	-
characteristic unconfined compressive strength (MPa)	40
	-

Tested as per AS/NZS 4456: 2003 and 4586: 2013.

*This data represents average results from production lots based on the results achieved by samples selected at random for testing.
Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification*