


## Product Details

range name	TERRE
finish	TUMBLED
colours	MARIGOLD
product code   description	###   400 X 400 X 40MM PAVERS

## Properties and Specifications

actual dimensions (length x width x height mm)	400 x 400 x 40mm
dimensional category	DPA2
average weight (KG)	12.55
durability class	General Purpose
number per sqm/lm	6.25
number per pallet	-
characteristics breaking load (kN)	8
mean cold water absorption (%)	2.5
mean abrasion resistance (CM <sup>3</sup> )	-
slip resistance category	P4
light reflectance value	-
	-
	-

## Diagram



*Tested as per AS/NZS 4456: 2003 and 4586: 2013.*

*This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification. \*please contact Urbanstone for installation requirements for Pool applications \*\*\*Endurastone Flamed and Terre range can be used around pools but should be sealed on top, bottom and sides of units (Please note. SA and WA Endurastone Flamed is presealed). \*\*\*\*this applies to installations on a concrete/mortar base using of pavers with a thickness of 40mm. Driveway paving with a maximum size of 400x400 and a minimum thickness of 60mm may be installed on a suitably designed flexible base.\*\*\*\*\*UrbanStone recommends the use of a suitable sealer around salt water swimming pools. Please note, that the application of a surface sealer may affect the slip rating of your pavement.*

## Product Details

range name	TERRE
finish	TUMBLED
colours	MARIGOLD
product code   description	###   600 X 400 X 30MM PAVERS

## Properties and Specifications

actual dimensions (length x width x height mm)	600 x 400 x 30mm
dimensional category	DPA2
average weight (KG)	19.365
durability class	General Purpose
number per sqm/lm	2.77
number per pallet	-
characteristics breaking load (kN)	4.1
mean cold water absorption (%)	2.6
mean abrasion resistance (CM <sup>3</sup> )	-
slip resistance category	P4
light reflectance value	-
	-
	-

## Diagram



*Tested as per AS/NZS 4456: 2003 and 4586: 2013.*

*This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification. \*please contact Urbanstone for installation requirements for Pool applications \*\*\*Endurastone Flamed and Terre range can be used around pools but should be sealed on top, bottom and sides of units (Please note. SA and WA Endurastone Flamed is presealed). \*\*\*\*this applies to installations on a concrete/mortar base using of pavers with a thickness of 40mm. Driveway paving with a maximum size of 400x400 and a minimum thickness of 60mm may be installed on a suitably designed flexible base.\*\*\*\*\*UrbanStone recommends the use of a suitable sealer around salt water swimming pools. Please note, that the application of a surface sealer may affect the slip rating of your pavement.*

## Product Details

range name	TERRE
finish	TUMBLED
colours	MARIGOLD
product code   description	###   1.44 SQM FRENCH PATTERN

## Properties and Specifications

actual dimensions (length x width x height mm)	1.44 SQM FRENCH PATTERN
dimensional category	DPA2
average weight (KG)	-
durability class	General Purpose
number per sqm/lm	-
number per pallet	-
characteristics breaking load (kN)	4.1
mean cold water absorption (%)	2.6
mean abrasion resistance (CM <sup>3</sup> )	-
slip resistance category	P4
light reflectance value	-
	-
	-

## Diagram



*Tested as per AS/NZS 4456: 2003 and 4586: 2013.*

*This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification. \*please contact Urbanstone for installation requirements for Pool applications \*\*\*Endurastone Flamed and Terre range can be used around pools but should be sealed on top, bottom and sides of units (Please note. SA and WA Endurastone Flamed is presealed). \*\*\*\*this applies to installations on a concrete/mortar base using of pavers with a thickness of 40mm. Driveway paving with a maximum size of 400x400 and a minimum thickness of 60mm may be installed on a suitably designed flexible base.\*\*\*\*\*UrbanStone recommends the use of a suitable sealer around salt water swimming pools. Please note, that the application of a surface sealer may affect the slip rating of your pavement.*