

## Product Details

range name	AUSTRALIAN GRANITE
finish	EXFOLIATED
colours	AUSTRAL JUPERANA, COFFEE & BLACK   GARNET ICE
product code   description	-  400 × 400 × 20MM

## Properties and Specifications

actual dimensions (length x width x height mm)	400 × 400 × 20mm
dimensional category	DPA2
average weight (KG)	9
durability class	General Purpose
number per sqm/lm	6.25
number per pallet	-
characteristic breaking load (kN)	-
mean cold water absorption (%)	2.7
mean abrasion resistance (CM³)	-
slip resistance category	P5
light reflectance value	Austral Black - 0.93, Austral Coffee - 0.60, Austral Juperana - 0.57 Desert Rose - 0.63, Garnet Ice - 0.69
	-
	-

## Diagram



Tested as per AS/NZS 4456: 2003 and 4586: 2013.

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification. \*please contact Urbanstone for installation requirements for Pool applications \*\*\*Endurastone Flamed and Terre range can be used around pools but should be sealed on top, bottom and sides of units (Please note. SA and WA Endurastone Flamed is presealed). \*\*\*\*this applies to installations on a concrete/mortar base using of pavers with a thickness of 40mm. Driveway paving with a maximum size of 400×400 and a minimum thickness of 60mm may be installed on a suitably designed flexible base.\*\*\*\*\*UrbanStone recommends the use of a suitable sealer around salt water swimming pools. Please note, that the application of a surface sealer may affect the slip rating of your pavement.


## Product Details

range name	AUSTRALIAN GRANITE
finish	HONED
colours	AUSTRAL JUPERANA, COFFEE & BLACK   GARNET ICE
product code   description	-  400 × 400 × 20MM

## Properties and Specifications

actual dimensions (length x width x height mm)	400 × 400 × 20mm
dimensional category	DPA2
average weight (KG)	9
durability class	General Purpose
number per sqm/lm	6.25
number per pallet	-
characteristic breaking load (kN)	-
mean cold water absorption (%)	2.7
mean abrasion resistance (CM³)	-
slip resistance category	P2
light reflectance value	Austral Black - 0.93, Austral Coffee - 0.60, Austral Juperana - 0.57 Desert Rose - 0.63, Garnet Ice - 0.69
	-
	-

## Diagram



Tested as per AS/NZS 4456: 2003 and 4586: 2013.

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification. \*please contact Urbanstone for installation requirements for Pool applications \*\*\*Endurastone Flamed and Terre range can be used around pools but should be sealed on top, bottom and sides of units (Please note. SA and WA Endurastone Flamed is presealed). \*\*\*\*this applies to installations on a concrete/mortar base using of pavers with a thickness of 40mm. Driveway paving with a maximum size of 400×400 and a minimum thickness of 60mm may be installed on a suitably designed flexible base.\*\*\*\*\*UrbanStone recommends the use of a suitable sealer around salt water swimming pools. Please note, that the application of a surface sealer may affect the slip rating of your pavement.

## Product Details

range name	AUSTRALIAN GRANITE
finish	EXFOLIATED
colours	AUSTRAL JUPERANA, COFFEE & BLACK   GARNET ICE
product code   description	-   600 × 150 × 20MM

## Properties and Specifications

actual dimensions (length x width x height mm)	600 × 150 × 20MM
dimensional category	DPA2
average weight (KG)	5
durability class	General Purpose
number per sqm/lm	11.11
number per pallet	-
characteristic breaking load (kN)	-
mean cold water absorption (%)	2.7
mean abrasion resistance (CM <sup>3</sup> )	-
slip resistance category	P5
light reflectance value	Austral Black - 0.93, Austral Coffee - 0.60, Austral Juperana - 0.57 Desert Rose - 0.63, Garnet Ice - 0.69
	-
	-

## Diagram



Tested as per AS/NZS 4456: 2003 and 4586: 2013.

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification. \*please contact Urbanstone for installation requirements for Pool applications \*\*\*Endurastone Flamed and Terre range can be used around pools but should be sealed on top, bottom and sides of units (Please note. SA and WA Endurastone Flamed is presealed). \*\*\*\*this applies to installations on a concrete/mortar base using of pavers with a thickness of 40mm. Driveway paving with a maximum size of 400×400 and a minimum thickness of 60mm may be installed on a suitably designed flexible base.\*\*\*\*\*UrbanStone recommends the use of a suitable sealer around salt water swimming pools. Please note, that the application of a surface sealer may affect the slip rating of your pavement.


## Product Details

range name	AUSTRALIAN GRANITE
finish	HONED
colours	AUSTRAL JUPERANA, COFFEE & BLACK   GARNET ICE
product code   description	-  600 × 150 × 20MM

## Properties and Specifications

actual dimensions (length x width x height mm)	600 × 150 × 20MM
dimensional category	DPA2
average weight (KG)	5
durability class	General Purpose
number per sqm/lm	11.11
number per pallet	-
characteristic breaking load (kN)	-
mean cold water absorption (%)	2.7
mean abrasion resistance (CM³)	-
slip resistance category	P2
light reflectance value	Austral Black - 0.93, Austral Coffee - 0.60, Austral Juperana - 0.57 Desert Rose - 0.63, Garnet Ice - 0.69
	-
	-

## Diagram



Tested as per AS/NZS 4456: 2003 and 4586: 2013.

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact UrbanStone for confirmation of product specification. \*please contact Urbanstone for installation requirements for Pool applications \*\*\*Endurastone Flamed and Terre range can be used around pools but should be sealed on top, bottom and sides of units (Please note. SA and WA Endurastone Flamed is presealed). \*\*\*\*this applies to installations on a concrete/mortar base using of pavers with a thickness of 40mm. Driveway paving with a maximum size of 400×400 and a minimum thickness of 60mm may be installed on a suitably designed flexible base.\*\*\*\*\*UrbanStone recommends the use of a suitable sealer around salt water swimming pools. Please note, that the application of a surface sealer may affect the slip rating of your pavement.